



FLOOR PLAN  
 $1\frac{1}{4}'' = 1'$   
 1322 SQ.FT. / SIDE

NOTES:

- 1 ALL DIMENSIONS ARE FACE OF STUD TO FACE OF STUD
- 2 ALL CLOSETS TO BE 25" DEEP
- 3 ALL EXTERIOR WALLS TO BE 2x6 (5 1/2")
- 4 ALL INTERIOR WALLS TO BE 2x4 (3 1/2")

BRACING LEGEND

CSWSP = "CONTINUOUS SHEATHED WSP" 3/8" FOR MAXIMUM 16" O.C. STUD SPACING  
 7/16" FOR 24" O.C. STUD SPACING. FASTENED w/ 5d COMMON NAIL  
 OR 8d BOX NAIL (21/2" LONG x .0113" DIA.), FASTENERS SPACED 6" EDGES, 12" FIELD

PF = "PORTAL FRAME" 12' MAX HT. REFER TO FIGURE 321.25 (A) FOR MINIMUM PANEL  
 WIDTH, MIN FASTENERS, & MAX FASTNER SPACING

BRACING NOTES:  
 CONTINUOUS BRACING METHOD USED  
 RECTANGLE SIZE IS 76' x 58'  
 SIDE PERPENDICULAR TO THE 76' SIDE REQUIRES 14'-11" OF BRACING  
 SIDE PERPENDICULAR TO THE 58' SIDE REQUIRES 11'-2" OF BRACING

WALL HEIGHT = 9'  
 EAVE - RIDGE HEIGHT = 13'  
 MAX. OPENING HEIGHT = 6'-8"  
 WIND EXP. = B  
 MIN. PANEL WIDTH = 30"  
 MIN. PF WIDTH = 18"

STEVE'S DRAFTING SERVICE ASSUMES NO RESPONSIBILITY  
 FOR THE ACCURACY OF THESE PLANS. WE DO NOT  
 PROVIDE ARCHITECTURAL OR ENGINEERING SERVICES.  
 WE PROVIDE A DRAFTING SERVICE ONLY.  
 E-MAIL: steve.s@charter.net  
 WEB: www.stevedraftingservice.com